

Ein Produkt von

minCam

vision meets precision

mc15set

With 13 or 18 mm camera head





Push-Pull version with 13 mm, push rod version with 18 mm camera head



mc15set


With 13 or 18 mm camera head

Sewer, water & drain video pipe inspection camera, cable reel and monitor.

The mc15 is a compact and durable CCTV push camera system. The Push-Pull version is one of the smallest cameras. The 5.6 mm push cable is super-flexible, and the KK18 camera is very bright. Application range is 15 mm to 125 mm. 512 Hz sonde or 33 kHz available for special order.

mc15	mc15 Push-Pull-Set for pipes from 15 to 80 mm	HH13	camera head
	<ul style="list-style-type: none"> • complete set with centre guide • cable reel out of stainless steel and carbon • camera head directly mounted with 10 cm Vario cable to 30 m Push-Pull cable • Control unit with function keys for Meter counter (optional sonde) • Continuous light regulation; battery status; video out • Internal power supply 100 – 240 V • 12 V DC Ladeeingang • 12 V car charger; battery > 2 h • Dimension: about 350 x 230 x 395 mm (l x w x h); 6.9kg 		<ul style="list-style-type: none"> • Directly mounted to Vario cable • High res color module • 480 TV-lines • 0.02 lux • view angle diagonal: 90° • 1 mm Sapphire glass protected lens • 3 bar water protected • Outer diameter: 13 mm • cylindrical length: 9 mm

mc15	Push-Pull-Set Rod for pipes from 30 to 125 mm	HH18	camera head
	<ul style="list-style-type: none"> • complete set with centre guide • cable reel out of stainless steel and carbon • 30 m / 5.8 mm push rod cable, changeable due to a special connector • Control unit with function keys for Meter counter (optional sonde) • Continuous light regulation; battery status; video out • Internal power supply 100 – 240 V • 12 V car charger; battery > 2 h • Dimension: about 350 x 230 x 395 mm (l x w x h); 6.9kg 		<ul style="list-style-type: none"> • High res color module • 480 TV-lines • 0.02 lux • view angle diagonal: 90° • 2 mm Sapphire glass protected lens • 5 bar water protected • Outer diameter: 18 mm • cylindrical length: 10 mm

mc15	monitor
	<ul style="list-style-type: none"> • 5.6" sunlight readable TFT-LCD monitor in a Carbon housing • mounted on reel with ball point joint • storage of videos, pictures and audio on SD-card – max. 32 GB • MPEG-4 video (*.avi; 800 x 600 pixel) • pictures (*.bmp; 640 x 480 pixel) • electronic insert of meter value, date text generator with external keyboard optional



minCam GmbH
Gruben 1 · 87561 Oberstdorf, Germany
Telefon +49 (0)8326 384122
info@minCam.de · www.minCam.de

EndoMatrix (M) Sdn Bhd
No. 51-5, Block G, Dataran Prima, Jalan PJU 1/37,
47301 Petaling Jaya, Selangor Darul Ehsan, Malaysia.
Phone: 03-7803 1145 | Fax: 03-9101 4814
sales@endomatrix.com.my | www.endomatrix.com.my